

4.8L - Cathedral Port	Bore	Comp Ht.	Stroke	Rod	0 deck at	Std. Deck Ht.	Volume	C.R. @ 61cc	C.R. @ 65cc	C.R. @ 68cc	C.R. @ 71cc	Pin (incl.)	Rings 1.5 1.5 3mm (not incl.)
4.8L Block - Standard Stroke - Standard Gen. 3 Press fit rod .945 pin													
SUM-326945780-7P	3.780	1.326	3.267	6.275	9.235	9.230-9.240	7cc Dish	8.9	8.5	8.2	8	Press Fit .945	SUM-136SM8531005
SUM-326945785-7P	3.785												SUM-136SM8531005
SUM-326945810-7P	3.810												SUM-136SM8531035
SUM-326945820-7P	3.820												SUM-136SM8531045
SUM-326945780-2P	3.780						2cc Dome	10	9.4	9.1	8.8		SUM-136SM8531005
SUM-326945785-2P	3.785												SUM-136SM8531005
SUM-326945810-2P	3.810												SUM-136SM8531035
SUM-326945820-2P	3.820												SUM-136SM8531045
4.8L Block - Standard Stroke - Standard Gen. 4 2004.5+ Rod - Full Floating .9431 pin													
SUM-326943780-7F	3.780	1.326	3.267	6.275	9.235	9.230-9.240	7cc Dish	8.9	8.5	8.2	8	Full Floating .9431	SUM-136SM8531005
SUM-326943785-7F	3.785												SUM-136SM8531005
SUM-326943810-7F	3.810												SUM-136SM8531035
SUM-326943820-7F	3.820												SUM-136SM8531045
SUM-326943780-2F	3.780						2cc Dome	10	9.4	9.1	8.8		SUM-136SM8531005
SUM-326943785-2F	3.785												SUM-136SM8531005
SUM-326943810-2F	3.810												SUM-136SM8531035
SUM-326943820-2F	3.820												SUM-136SM8531045