



Summit Pro LS Forged Pistons - 5.7L Cathedral Port

5.7L - Cathedral Port	Bore	Comp Ht.	Stroke	Rod	0 deck at	Std. Deck Ht.	Volume	C.R. @ 61cc	C.R. @ 65cc	C.R. @ 68cc	C.R. @ 71cc	Pin (incl.)	Rings 1.2 1.2 3mm (not incl.)
5.7L Block - Standard Stroke - Standard Gen. 3 Press-fit rod .945 pin													
SUM-3269453898-3	3.898	1.326	3.622	6.098	9.235	9.240	3cc Dome	11.6	11	10.6	10.2	Press fit 0.945	SUM-136SN9035STD
SUM-3269453903-3	3.903												SUM-136SN9035007
5.7L Block - Standard Stroke - Aftermarket 6.125 Rod - .927 pin													
SUM-2999273898-7	3.898	1.299	3.622	6.125	9.235	9.240	7cc Dish	10.2	9.7	9.5	9.2	Full Floating 0.927	SUM-136SN9035STD
SUM-2999273903-7	3.903						SUM-136SN9035007						
SUM-2999273898-3	3.898						3cc Dome	11.6	11	10.6	10.2		SUM-136SN9035STD
SUM-2999273903-3	3.903						SUM-136SN9035007						
5.7L Block - 4.000 in Stroker - Aftermarket 6.125 Rod - .927 pin													
SUM-110927389816	3.898	1.110	4.000	6.125	9.235	9.240	16cc Dish	10.1	9.7	9.5	9.2	Full Floating 0.927	SUM-136SN9035STD
SUM-110927390316	3.903						SUM-136SN9035007						
SUM-1109273903-5	3.903						5cc Spherical Dish	11.5	11	10.6	10.2		SUM-136SN9035007