

Engine: *LS*

Grind # : *LLSR 248-390-258-382-15*

Core : *3310163*

Lobe size bc/ht IN: EX:

Enter (2) : 2

Camshaft Data= 5 CRNK DEG

DURATION AT .05 IN

INTAKE - Rocker Ratio= 1.7
Lash 23 24 25 0

IN

.000 Cold

EXHAUST - Rocker Ratio= 1.7
Lash 23 24 25 0

IN

.010 Hot

INSTALL CAM ON * * below Cyl# 1

Intake & Exhaust

LOBE SEPERATION = 115.1 CAM DEG
valve overlap= 23 CRANK DEG

INTAKE

valve open = 14.1 'BTDC
* CENTERLINE---> 110.1 'ATDC
valve close= 54.3 'ABDC
DURATION-----> 248.3 CRANK DEG
lobe lift= .39008 IN.
VALVE LIFT---> .66313 IN.
lobe area= 32.91 IN * DEG

EXHAUST

valve open = 69.6 'BBDC
* CENTERLINE---> 120.1 'BTDC
valve close= 8.9 'ATDC
DURATION-----> 258.5 CRANK DEG
lobe lift= .38205 IN.
VALVE LIFT---> .64948 IN.
lobe area= 33.99 IN * DEG